

The xtable gallery

Jonathan Swinton <jonathan@swintons.net>
with small contributions from others

November 6, 2009

1 Summary

This document gives a gallery of tables which can be made by using the `xtable` package to create L^AT_EX output. It doubles as a regression check for the package.

```
> library(xtable)
```

2 Gallery

2.1 Data frame

Load example dataset

```
> data(tli)
> tli.table <- xtable(tli[1:10, ])
> digits(tli.table)[c(2, 6)] <- 0
> print(tli.table, floating = FALSE)
```

	grade	sex	disadv	ethnicity	timth
1	6	M	YES	HISPANIC	43
2	7	M	NO	BLACK	88
3	5	F	YES	HISPANIC	34
4	3	M	YES	HISPANIC	65
5	8	M	YES	WHITE	75
6	5	M	NO	BLACK	74
7	8	F	YES	HISPANIC	72
8	4	M	YES	BLACK	79
9	6	M	NO	WHITE	88
10	7	M	YES	HISPANIC	87

2.2 Matrix

```
> design.matrix <- model.matrix(~sex * grade, data = tli[1:10,
+ ])
> design.table <- xtable(design.matrix)
> print(design.table, floating = FALSE)
```

	(Intercept)	sexM	grade	sexM:grade
1	1.00	1.00	6.00	6.00
2	1.00	1.00	7.00	7.00
3	1.00	0.00	5.00	0.00
4	1.00	1.00	3.00	3.00
5	1.00	1.00	8.00	8.00
6	1.00	1.00	5.00	5.00
7	1.00	0.00	8.00	0.00
8	1.00	1.00	4.00	4.00
9	1.00	1.00	6.00	6.00
10	1.00	1.00	7.00	7.00

2.3 aov

```
> fm1 <- aov(tlimth ~ sex + ethnicity + grade + disadvg, data = tli)
> fm1.table <- xtable(fm1)
> print(fm1.table, floating = FALSE)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
sex	1	75.37	75.37	0.38	0.5417
ethnicity	3	2572.15	857.38	4.27	0.0072
grade	1	36.31	36.31	0.18	0.6717
disadvg	1	59.30	59.30	0.30	0.5882
Residuals	93	18682.87	200.89		

2.4 lm

```
> fm2 <- lm(tlimth ~ sex * ethnicity, data = tli)
> fm2.table <- xtable(fm2)
> print(fm2.table, floating = FALSE)
```

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	73.6364	4.2502	17.33	0.0000
sexM	-1.6364	5.8842	-0.28	0.7816
ethnicityHISPANIC	-9.7614	6.5501	-1.49	0.1395
ethnicityOTHER	15.8636	10.8360	1.46	0.1466
ethnicityWHITE	4.7970	4.9687	0.97	0.3368
sexM:ethnicityHISPANIC	10.6780	8.7190	1.22	0.2238
sexM:ethnicityWHITE	5.1230	7.0140	0.73	0.4670

2.4.1 anova object

```
> print(xtable(anova(fm2)), floating = FALSE)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
sex	1	75.37	75.37	0.38	0.5395
ethnicity	3	2572.15	857.38	4.31	0.0068
sex:ethnicity	2	298.43	149.22	0.75	0.4748
Residuals	93	18480.04	198.71		

2.4.2 Another anova object

```
> fm2b <- lm(tlimth ~ ethnicity, data = tli)
```

```
> print(xtable(anova(fm2b, fm2)), floating = FALSE)
```

	Res.Df	RSS	Df	Sum of Sq	F	Pr(>F)
1	96	19053.59				
2	93	18480.04	3	573.55	0.96	0.4141

2.5 glm

```
> fm3 <- glm(disadv ~ ethnicity * grade, data = tli, family = binomial())
```

```
> fm3.table <- xtable(fm3)
```

```
> print(fm3.table, floating = FALSE)
```

	Estimate	Std. Error	z value	Pr(> z)
(Intercept)	3.1888	1.5966	2.00	0.0458
ethnicityHISPANIC	-0.2848	2.4808	-0.11	0.9086
ethnicityOTHER	212.1701	22122.7093	0.01	0.9923
ethnicityWHITE	-8.8150	3.3355	-2.64	0.0082
grade	-0.5308	0.2892	-1.84	0.0665
ethnicityHISPANIC:grade	0.2448	0.4357	0.56	0.5742
ethnicityOTHER:grade	-32.6014	3393.4687	-0.01	0.9923
ethnicityWHITE:grade	1.0171	0.5185	1.96	0.0498

2.5.1 anova object

```
> print(xtable(anova(fm3)), floating = FALSE)
```

	Df	Deviance	Resid. Df	Resid. Dev
NULL			99	129.49
ethnicity	3	47.24	96	82.25
grade	1	1.73	95	80.52
ethnicity:grade	3	7.20	92	73.32

2.6 More aov

```
> N <- c(0, 1, 0, 1, 1, 1, 0, 0, 0, 1, 1, 0, 1, 1, 0, 0, 1, 0,
+       1, 0, 1, 1, 0, 0)
> P <- c(1, 1, 0, 0, 0, 1, 0, 1, 1, 1, 0, 0, 0, 1, 0, 1, 1, 0,
+       0, 1, 0, 1, 1, 0)
> K <- c(1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 0, 1, 0, 1, 1, 0, 0, 0,
+       1, 1, 1, 0, 1, 0)
> yield <- c(49.5, 62.8, 46.8, 57, 59.8, 58.5, 55.5, 56, 62.8,
+           55.8, 69.5, 55, 62, 48.8, 45.5, 44.2, 52, 51.5, 49.8, 48.8,
+           57.2, 59, 53.2, 56)
> npk <- data.frame(block = gl(6, 4), N = factor(N), P = factor(P),
+                   K = factor(K), yield = yield)
> npk.aov <- aov(yield ~ block + N * P * K, npk)
> op <- options(contrasts = c("contr.helmert", "contr.treatment"))
> npk.aovE <- aov(yield ~ N * P * K + Error(block), npk)
> options(op)

> print(xtable(npk.aov), floating = FALSE)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
block	5	343.29	68.66	4.45	0.0159
N	1	189.28	189.28	12.26	0.0044
P	1	8.40	8.40	0.54	0.4749
K	1	95.20	95.20	6.17	0.0288
N:P	1	21.28	21.28	1.38	0.2632
N:K	1	33.13	33.13	2.15	0.1686
P:K	1	0.48	0.48	0.03	0.8628
Residuals	12	185.29	15.44		

2.6.1 anova object

```
> print(xtable(anova(npk.aov)), floating = FALSE)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
block	5	343.29	68.66	4.45	0.0159
N	1	189.28	189.28	12.26	0.0044
P	1	8.40	8.40	0.54	0.4749
K	1	95.20	95.20	6.17	0.0288
N:P	1	21.28	21.28	1.38	0.2632
N:K	1	33.13	33.13	2.15	0.1686
P:K	1	0.48	0.48	0.03	0.8628
Residuals	12	185.29	15.44		

2.6.2 Another anova object

```
> print(xtable(summary(npk.aov)), floating = FALSE)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
block	5	343.29	68.66	4.45	0.0159
N	1	189.28	189.28	12.26	0.0044
P	1	8.40	8.40	0.54	0.4749
K	1	95.20	95.20	6.17	0.0288
N:P	1	21.28	21.28	1.38	0.2632
N:K	1	33.13	33.13	2.15	0.1686
P:K	1	0.48	0.48	0.03	0.8628
Residuals	12	185.29	15.44		

```
> print(xtable(npk.aovE), floating = FALSE)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
N:P:K	1	37.00	37.00	0.48	0.5252
Residuals	4	306.29	76.57		
N	1	189.28	189.28	12.26	0.0044
P	1	8.40	8.40	0.54	0.4749
K	1	95.20	95.20	6.17	0.0288
N:P	1	21.28	21.28	1.38	0.2632
N:K	1	33.14	33.14	2.15	0.1686
P:K	1	0.48	0.48	0.03	0.8628
Residuals1	12	185.29	15.44		

```
> print(xtable(summary(npk.aovE)), floating = FALSE)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
N:P:K	1	37.00	37.00	0.48	0.5252
Residuals	4	306.29	76.57		
N	1	189.28	189.28	12.26	0.0044
P	1	8.40	8.40	0.54	0.4749
K	1	95.20	95.20	6.17	0.0288
N:P	1	21.28	21.28	1.38	0.2632
N:K	1	33.14	33.14	2.15	0.1686
P:K	1	0.48	0.48	0.03	0.8628
Residuals1	12	185.29	15.44		

2.7 More lm

```
> ctl <- c(4.17, 5.58, 5.18, 6.11, 4.5, 4.61, 5.17, 4.53, 5.33,
+         5.14)
> trt <- c(4.81, 4.17, 4.41, 3.59, 5.87, 3.83, 6.03, 4.89, 4.32,
+         4.69)
> group <- gl(2, 10, 20, labels = c("Ctl", "Trt"))
> weight <- c(ctl, trt)
> lm.D9 <- lm(weight ~ group)

> print(xtable(lm.D9), floating = FALSE)
```

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	5.0320	0.2202	22.85	0.0000
groupTrt	-0.3710	0.3114	-1.19	0.2490

```
> print(xtable(anova(lm.D9)), floating = FALSE)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
group	1	0.69	0.69	1.42	0.2490
Residuals	18	8.73	0.48		

2.8 More glm

```
> counts <- c(18, 17, 15, 20, 10, 20, 25, 13, 12)
> outcome <- gl(3, 1, 9)
> treatment <- gl(3, 3)
> d.AD <- data.frame(treatment, outcome, counts)
> glm.D93 <- glm(counts ~ outcome + treatment, family = poisson())
> print(xtable(glm.D93, align = "r/l/lrc"), floating = FALSE)
```

	Estimate	Std. Error	z value	Pr(> z)
(Intercept)	3.0445	0.1709	17.81	0.0000
outcome2	-0.4543	0.2022	-2.25	0.0246
outcome3	-0.2930	0.1927	-1.52	0.1285
treatment2	0.0000	0.2000	0.00	1.0000
treatment3	0.0000	0.2000	0.00	1.0000

2.9 prcomp

```
> if (require(stats, quietly = TRUE)) {
+   data(USArrests)
+   pr1 <- prcomp(USArrests)
+ }
> if (require(stats, quietly = TRUE)) {
+   print(xtable(pr1), floating = FALSE)
+ }
```

	PC1	PC2	PC3	PC4
Murder	0.0417	-0.0448	0.0799	-0.9949
Assault	0.9952	-0.0588	-0.0676	0.0389
UrbanPop	0.0463	0.9769	-0.2005	-0.0582
Rape	0.0752	0.2007	0.9741	0.0723

```
> print(xtable(summary(pr1)), floating = FALSE)
```

	PC1	PC2	PC3	PC4
Standard deviation	83.7324	14.2124	6.4894	2.4828
Proportion of Variance	0.9655	0.0278	0.0058	0.0008
Cumulative Proportion	0.9655	0.9933	0.9991	1.0000

2.10 Time series

```
> temp.ts <- ts(cumsum(1 + round(rnorm(100), 0)), start = c(1954,
+ 7), frequency = 12)
> temp.table <- xtable(temp.ts, digits = 0)
> caption(temp.table) <- "Time series example"

> print(temp.table, floating = FALSE)
```

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1954							-1	-1	0	3	4	5
1955	5	5	4	4	3	4	4	5	6	7	7	8
1956	8	9	9	12	13	14	14	16	16	17	17	19
1957	21	23	25	28	28	30	32	34	34	35	35	36
1958	37	38	39	41	44	44	43	43	44	45	45	46
1959	48	48	49	51	51	51	52	52	53	52	53	56
1960	59	59	60	61	62	63	63	65	65	66	67	67
1961	69	70	73	75	76	75	78	80	79	80	79	81
1962	82	84	87	89	90	92	93	96	98	100		

3 Sanitization

```
> insane <- data.frame(Name = c("Ampersand", "Greater than", "Less than",
+ "Underscore", "Per cent", "Dollar", "Backslash", "Hash",
+ "Caret", "Tilde", "Left brace", "Right brace"), Character = I(c("&",
+ ">", "<", "_", "%", "$", "\\\"", "#", "^", "~", "{", "}")))
> colnames(insane)[2] <- paste(insane[, 2], collapse = "")

> print(xtable(insane))
```

	Name	&><_-%\$\\#^~{}
1	Ampersand	&
2	Greater than	>
3	Less than	<
4	Underscore	_
5	Per cent	%
6	Dollar	\$
7	Backslash	\
8	Hash	#
9	Caret	^
10	Tilde	~
11	Left brace	{
12	Right brace	}

Sometimes you might want to have your own sanitization function

```

> wanttex <- xtable(data.frame(label = paste("Value_is $10^{-",
+     1:3, "}$", sep = "")))
> print(wanttex, sanitize.text.function = function(str) gsub("-",
+     "\\_", str, fixed = TRUE))

```

	label
1	Value_is 10^{-1}
2	Value_is 10^{-2}
3	Value_is 10^{-3}

3.1 Markup in tables

Markup can be kept in tables, including column and row names, by using a custom `sanitize.text.function`:

```

> mat <- round(matrix(c(0.9, 0.89, 200, 0.045, 2), c(1, 5)), 4)
> rownames(mat) <- "$y_{t-1}$"
> colnames(mat) <- c("$R^2$", "$\\bar{R}^2$", "F-stat", "S.E.E",
+     "DW")
> mat <- xtable(mat)

> print(mat, sanitize.text.function = function(x) {
+     x
+ })

```

	R^2	\bar{R}^2	F-stat	S.E.E	DW
y_{t-1}	0.90	0.89	200.00	0.04	2.00

You can also have sanitize functions that are specific to column or row names. In the table below, the row name is not sanitized but column names and table elements are:

```

> money <- matrix(c("$1,000", "$900", "$100"), ncol = 3, dimnames = list("$\\alpha$",
+     c("Income (US$)", "Expenses (US$)", "Profit (US$)")))
> print(xtable(money), sanitize.rownames.function = function(x) {
+     x
+ })

```


	Income (US\$)	Expenses (US\$)	Profit (US\$)
α	\$1,000	\$900	\$100

4 Format examples

4.1 Adding a centering environment

```
> print(xtable(lm.D9, caption = "\\tt latex.environment=NULL"),
+       latex.environment = NULL)
```

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	5.0320	0.2202	22.85	0.0000
groupTrt	-0.3710	0.3114	-1.19	0.2490

Table 1: latex.environment=NULL

```
> print(xtable(lm.D9, caption = "\\tt latex.environment=\"\""),
+       latex.environment = "")
```

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	5.0320	0.2202	22.85	0.0000
groupTrt	-0.3710	0.3114	-1.19	0.2490

Table 2: latex.environment=""

```
> print(xtable(lm.D9, caption = "\\tt latex.environment=\"center\""),
+       latex.environment = "center")
```

4.2 Column alignment

```
> tli.table <- xtable(tli[1:10, ])
> align(tli.table) <- rep("r", 6)
> print(tli.table, floating = FALSE)
```

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	5.0320	0.2202	22.85	0.0000
groupTrt	-0.3710	0.3114	-1.19	0.2490

Table 3: `latex.environment="center"`

	grade	sex	disadv	ethnicity	timth
1	6	M	YES	HISPANIC	43
2	7	M	NO	BLACK	88
3	5	F	YES	HISPANIC	34
4	3	M	YES	HISPANIC	65
5	8	M	YES	WHITE	75
6	5	M	NO	BLACK	74
7	8	F	YES	HISPANIC	72
8	4	M	YES	BLACK	79
9	6	M	NO	WHITE	88
10	7	M	YES	HISPANIC	87

4.2.1 Single string and column lines

```
> align(tli.table) <- "|rrl|l|lr|"
> print(tli.table, floating = FALSE)
```

	grade	sex	disadv	ethnicity	timth
1	6	M	YES	HISPANIC	43
2	7	M	NO	BLACK	88
3	5	F	YES	HISPANIC	34
4	3	M	YES	HISPANIC	65
5	8	M	YES	WHITE	75
6	5	M	NO	BLACK	74
7	8	F	YES	HISPANIC	72
8	4	M	YES	BLACK	79
9	6	M	NO	WHITE	88
10	7	M	YES	HISPANIC	87

4.2.2 Fixed width columns

```
> align(tli.table) <- "|rr|lp{3cm}l|r|"
> print(tli.table, floating = FALSE)
```

	grade	sex	disadv	ethnicity	timth
1	6	M	YES	HISPANIC	43
2	7	M	NO	BLACK	88
3	5	F	YES	HISPANIC	34
4	3	M	YES	HISPANIC	65
5	8	M	YES	WHITE	75
6	5	M	NO	BLACK	74
7	8	F	YES	HISPANIC	72
8	4	M	YES	BLACK	79
9	6	M	NO	WHITE	88
10	7	M	YES	HISPANIC	87

4.3 Significant digits

Specify with a single argument

```
> digits(tli.table) <- 3
> print(tli.table, floating = FALSE, )
```

	grade	sex	disadv	ethnicity	timth
1	6	M	YES	HISPANIC	43
2	7	M	NO	BLACK	88
3	5	F	YES	HISPANIC	34
4	3	M	YES	HISPANIC	65
5	8	M	YES	WHITE	75
6	5	M	NO	BLACK	74
7	8	F	YES	HISPANIC	72
8	4	M	YES	BLACK	79
9	6	M	NO	WHITE	88
10	7	M	YES	HISPANIC	87

or one for each column, counting the row names

```
> digits(tli.table) <- 1:(ncol(tli) + 1)
> print(tli.table, floating = FALSE, )
```

	grade	sex	disadv	ethnicity	timth
1	6	M	YES	HISPANIC	43
2	7	M	NO	BLACK	88
3	5	F	YES	HISPANIC	34
4	3	M	YES	HISPANIC	65
5	8	M	YES	WHITE	75
6	5	M	NO	BLACK	74
7	8	F	YES	HISPANIC	72
8	4	M	YES	BLACK	79
9	6	M	NO	WHITE	88
10	7	M	YES	HISPANIC	87

or as a full matrix

```
> digits(tli.table) <- matrix(0:4, nrow = 10, ncol = ncol(tli) +
+   1)
> print(tli.table, floating = FALSE, )
```

	grade	sex	disadv	ethnicity	tlimth
1	6	M	YES	HISPANIC	43
2	7	M	NO	BLACK	88
3	5	F	YES	HISPANIC	34
4	3	M	YES	HISPANIC	65
5	8	M	YES	WHITE	75
6	5	M	NO	BLACK	74
7	8	F	YES	HISPANIC	72
8	4	M	YES	BLACK	79
9	6	M	NO	WHITE	88
10	7	M	YES	HISPANIC	87

4.4 Suppress row names

```
> print((tli.table), include.rownames = FALSE, floating = FALSE)
```

grade	sex	disadv	ethnicity	tlimth
6	M	YES	HISPANIC	43
7	M	NO	BLACK	88
5	F	YES	HISPANIC	34
3	M	YES	HISPANIC	65
8	M	YES	WHITE	75
5	M	NO	BLACK	74
8	F	YES	HISPANIC	72
4	M	YES	BLACK	79
6	M	NO	WHITE	88
7	M	YES	HISPANIC	87

If you want a vertical line on the left, you need to change the align attribute.

```
> align(tli.table) <- "|r|r|lp{3cm}l|r|"
> print((tli.table), include.rownames = FALSE, floating = FALSE)
```

grade	sex	disadv	ethnicity	tlimth
6	M	YES	HISPANIC	43
7	M	NO	BLACK	88
5	F	YES	HISPANIC	34
3	M	YES	HISPANIC	65
8	M	YES	WHITE	75
5	M	NO	BLACK	74
8	F	YES	HISPANIC	72
4	M	YES	BLACK	79
6	M	NO	WHITE	88
7	M	YES	HISPANIC	87

Revert the alignment to what is was before.

```
> align(tli.table) <- "|rr|lp{3cm}l|r|"
```

4.5 Suppress column names

```
> print((tli.table), include.colnames = FALSE, floating = FALSE)
```

1	6	M	YES	HISPANIC	43
2	7	M	NO	BLACK	88
3	5	F	YES	HISPANIC	34
4	3	M	YES	HISPANIC	65
5	8	M	YES	WHITE	75
6	5	M	NO	BLACK	74
7	8	F	YES	HISPANIC	72
8	4	M	YES	BLACK	79
9	6	M	NO	WHITE	88
10	7	M	YES	HISPANIC	87

Note the doubled header lines which can be suppressed with, eg,

```
> print(tli.table, include.colnames = FALSE, floating = FALSE,  
+       hline.after = c(0, nrow(tli.table)))
```

1	6	M	YES	HISPANIC	43
2	7	M	NO	BLACK	88
3	5	F	YES	HISPANIC	34
4	3	M	YES	HISPANIC	65
5	8	M	YES	WHITE	75
6	5	M	NO	BLACK	74
7	8	F	YES	HISPANIC	72
8	4	M	YES	BLACK	79
9	6	M	NO	WHITE	88
10	7	M	YES	HISPANIC	87

4.6 Suppress row and column names

```
> print((tli.table), include.colnames = FALSE, include.rownames = FALSE,  
+       floating = FALSE)
```

6	M	YES	HISPANIC	43
7	M	NO	BLACK	88
5	F	YES	HISPANIC	34
3	M	YES	HISPANIC	65
8	M	YES	WHITE	75
5	M	NO	BLACK	74
8	F	YES	HISPANIC	72
4	M	YES	BLACK	79
6	M	NO	WHITE	88
7	M	YES	HISPANIC	87

4.7 Horizontal lines

```
> print(xtable(anova(glm.D93)), hline.after = c(1), floating = FALSE)
```

	Df	Deviance	Resid. Df	Resid. Dev
NULL			8	10.58
outcome	2	5.45	6	5.13
treatment	2	0.00	4	5.13

4.8 Table-level L^AT_EX

```
> print(xtable(anova(glm.D93)), size = "small", floating = FALSE)
```

	Df	Deviance	Resid. Df	Resid. Dev
NULL			8	10.58
outcome	2	5.45	6	5.13
treatment	2	0.00	4	5.13

4.9 Long tables

Remember to insert `\usepackage{longtable}` in your LaTeX preamble. See Table 4.

```
> x <- matrix(rnorm(1000), ncol = 10)
> x.big <- xtable(x, label = "tabbig", caption = "Example of longtable spanning several pages")
> print(x.big, tabular.environment = "longtable", floating = FALSE)
```

	1	2	3	4	5	6	7	8	9	10
1	0.17	0.60	-0.73	2.50	0.87	0.31	0.64	-1.02	-0.94	0.13
2	-0.32	-0.13	-0.13	0.46	-0.13	0.50	-1.03	1.28	0.90	0.18
3	0.50	-0.51	2.27	2.12	1.17	-0.11	-1.11	-0.10	-1.30	1.51
4	1.04	1.08	-0.44	-0.30	0.47	-0.03	1.28	-0.59	-0.11	-0.92
5	-0.77	-1.16	-0.22	0.32	0.92	0.51	1.68	-1.41	0.12	0.92
6	1.21	-0.11	-1.32	0.74	0.85	-0.23	0.12	-0.67	-0.87	-0.20
7	-1.02	-0.42	-1.39	1.12	1.35	0.13	0.90	-0.54	-0.72	-0.85
8	-0.23	-1.74	1.81	0.21	2.88	0.13	-0.25	0.57	-1.24	0.01
9	0.75	-1.94	0.05	-1.18	-0.53	-0.30	0.27	2.20	-0.68	-0.11
10	1.04	-0.85	-0.15	0.12	0.11	-1.18	-0.83	1.02	0.58	-0.24
11	0.57	-0.82	0.44	0.85	0.99	-1.13	1.42	0.14	0.62	0.72
12	0.63	-0.60	0.62	1.07	0.74	-0.41	-0.25	0.14	1.10	-0.27
13	0.08	0.06	0.63	-1.77	-0.38	0.23	-0.22	-0.94	-0.92	-0.41
14	0.37	1.23	-0.16	2.59	0.96	0.39	0.37	1.44	-0.69	-1.55
15	-0.22	0.41	1.10	-1.03	0.82	1.69	-1.80	1.09	-0.60	-0.21
16	0.40	-0.40	-0.23	0.66	-1.25	0.29	-1.42	-0.04	0.26	0.57
17	1.03	-0.25	0.68	-0.64	-1.44	1.72	0.38	1.94	-0.49	-0.14
18	-0.30	-0.04	-0.87	1.26	1.06	-0.57	0.51	0.80	0.56	-0.27

19	-1.11	-0.91	1.62	-1.96	-1.26	-0.29	0.63	0.69	0.37	-0.45
20	-1.49	-1.69	-0.39	-0.81	0.44	0.50	0.32	1.07	-0.22	0.75
21	-1.11	-1.25	1.20	0.53	-0.43	-0.64	-2.64	-0.06	0.73	-0.07
22	0.70	-1.28	1.46	-1.52	1.37	0.58	-1.25	0.30	1.49	0.40
23	-1.86	0.40	1.55	-2.04	-0.27	0.95	-1.29	-0.27	-1.59	-0.74
24	-1.06	0.91	-0.77	-2.86	-0.70	-0.26	-0.82	0.67	0.70	-0.95
25	0.30	-0.27	1.10	-0.35	0.31	0.49	-0.78	0.01	1.80	-2.56
26	-1.79	0.38	-0.98	-0.33	-0.89	0.09	0.82	1.02	0.82	0.57
27	-1.39	0.17	-0.96	-1.08	0.76	0.25	0.89	-3.11	-0.68	1.02
28	0.26	-0.40	1.13	0.17	0.53	0.38	0.81	0.83	-1.04	-0.23
29	-0.07	0.52	0.73	0.60	0.21	-0.69	-0.31	0.86	0.55	-0.60
30	-1.04	0.70	-0.65	0.92	0.16	-0.48	1.30	0.30	0.49	-0.12
31	2.18	1.53	0.45	1.38	-0.46	-1.86	-0.72	0.09	0.01	-0.75
32	1.45	-0.53	-0.60	-1.01	0.44	-1.20	1.24	-0.05	-1.63	0.16
33	-0.43	1.12	0.02	0.18	2.95	-0.50	0.32	-0.06	2.13	-0.75
34	-0.50	-0.01	-1.55	-2.03	1.51	0.43	-0.03	0.49	0.18	0.42
35	-0.09	-0.53	-0.14	1.11	0.35	0.05	0.51	0.88	-1.18	-0.14
36	-1.29	1.06	0.95	-0.64	1.12	1.78	-0.47	0.72	0.16	-1.84
37	-1.14	-0.20	0.41	0.25	0.83	-1.24	0.22	-0.76	-0.16	-0.20
38	0.05	-0.58	0.23	0.73	-1.66	-1.28	0.72	-1.32	-0.29	-1.14
39	0.09	-0.44	-0.70	0.06	-0.86	0.16	0.82	-0.41	-0.33	-2.35
40	0.57	-1.90	0.39	-0.30	0.70	-1.02	-0.79	1.51	-1.34	0.96
41	1.02	-0.06	-1.77	-0.96	1.20	-1.55	-0.38	0.19	0.98	-1.07
42	1.71	-0.00	0.18	-0.79	0.13	0.14	-1.84	-1.28	1.78	0.15
43	0.45	-0.68	-1.99	-0.06	1.80	-1.64	-0.98	1.45	-0.68	0.64
44	0.67	-0.27	1.07	-0.42	-0.55	-0.79	0.93	0.24	1.94	0.11
45	-0.93	-0.76	-2.23	0.26	2.00	1.75	0.73	-1.34	-0.43	-0.57
46	0.17	-0.54	-0.63	0.80	0.60	0.52	-0.43	-1.21	0.02	-1.69
47	-0.25	-0.15	0.35	0.68	-0.98	0.44	-0.40	0.52	1.68	-0.27
48	-1.69	-0.74	-0.23	1.39	-0.20	-0.53	0.36	-2.12	0.66	-2.06
49	0.43	-0.57	2.44	-0.21	-0.22	-0.70	-0.14	-0.31	0.02	0.53
50	-1.11	0.52	1.68	-0.34	1.39	-0.19	-0.83	0.96	-0.12	0.00
51	-0.79	-1.76	-0.02	-1.58	0.28	-1.02	-0.34	-0.85	0.44	0.13
52	0.73	-1.52	-0.54	-1.55	-1.00	-0.09	0.91	0.31	0.65	0.78
53	-0.42	0.56	0.05	-0.47	0.38	0.78	-0.93	0.00	-2.44	-0.23
54	0.47	0.69	-0.61	-0.45	-2.13	-0.52	0.35	-0.72	-1.40	-0.62
55	0.04	0.86	-1.36	-0.11	2.23	0.83	0.50	-0.52	2.21	0.48
56	-1.22	-0.91	-1.67	1.41	-2.10	-0.94	-0.40	-1.91	0.45	0.19
57	-1.12	0.36	-1.26	-1.29	-0.03	-1.09	1.75	-0.31	-0.32	0.88
58	-1.36	-0.21	-0.79	0.10	-0.02	-0.78	0.50	-1.14	-1.02	-1.10
59	-0.76	-0.73	-0.84	0.36	1.62	-0.42	-0.27	0.38	-0.05	-1.32
60	-0.41	-0.35	0.32	0.57	1.02	-0.51	-0.91	-0.36	0.82	0.02
61	0.19	0.03	0.34	0.10	1.35	-0.47	-1.23	0.45	0.80	-0.08
62	-1.82	-0.12	-0.83	0.81	0.70	1.16	0.30	-0.02	-0.17	0.05
63	0.36	0.30	1.00	-2.68	-1.52	-0.27	-0.20	1.54	-2.77	-2.14
64	-1.30	0.26	-0.40	-0.60	0.76	-0.06	-0.34	-0.76	1.02	-0.75

65	-0.55	-0.94	2.18	0.23	0.87	1.20	0.02	0.87	-0.16	0.47
66	1.63	-0.03	-0.70	0.09	-0.05	-0.10	-1.51	-0.95	1.68	0.57
67	-0.75	-0.51	1.60	-1.19	0.54	-1.07	-0.25	0.42	1.25	-0.94
68	-1.45	-0.11	-0.45	0.34	-1.04	-0.72	0.58	0.66	-0.11	-0.39
69	0.05	0.94	-0.31	-0.03	-1.26	1.16	0.22	0.48	-2.54	-2.45
70	0.62	-0.39	0.37	-0.68	-0.98	-1.35	-0.99	0.04	0.15	0.04
71	-0.04	-1.82	0.46	0.22	-1.43	0.01	-0.14	0.21	0.88	1.09
72	0.51	0.30	0.79	0.82	0.58	0.56	0.71	-0.38	-0.23	-0.44
73	0.17	-0.35	0.57	0.77	-1.25	1.87	0.33	-0.27	-1.59	-0.12
74	-0.63	0.34	1.03	-1.23	-0.51	-0.07	-0.09	0.58	-1.31	-0.39
75	1.64	1.17	1.45	-2.43	1.74	-1.38	0.05	-0.62	-0.02	0.22
76	-1.23	-0.80	0.76	1.08	0.95	3.03	-1.15	-0.54	-2.73	-0.22
77	1.07	0.68	0.47	-3.11	0.23	-1.36	0.31	0.37	1.05	-0.12
78	2.64	-0.73	0.30	1.34	-0.35	-0.03	0.79	1.55	1.83	-0.38
79	-0.69	-0.85	0.68	0.03	1.60	-0.36	0.27	0.97	0.09	0.50
80	0.98	0.23	-1.15	0.23	0.26	-0.08	-0.61	0.47	0.84	-0.15
81	-0.97	0.39	-1.37	1.04	-0.07	-0.07	0.24	1.37	-0.28	-0.93
82	0.30	-0.13	-0.28	-1.26	-0.57	-1.78	0.02	0.36	-0.81	0.82
83	0.29	-0.62	1.18	0.92	1.65	-1.05	0.04	0.54	0.24	-0.08
84	-1.99	0.18	-1.61	1.36	0.23	-1.13	-1.26	0.23	1.60	0.81
85	1.26	-1.58	0.92	-0.46	0.41	-0.84	-1.40	-0.56	0.92	1.35
86	1.39	2.29	-0.50	0.17	-1.80	-0.07	-0.27	-1.42	-0.76	1.20
87	-0.47	0.94	-0.14	-1.33	-1.47	-1.06	-0.35	-0.12	0.01	1.92
88	-1.35	-2.10	-0.18	-0.74	0.95	-0.64	-0.62	-0.52	-0.87	0.17
89	-0.27	0.37	-0.13	1.12	1.17	0.38	-0.40	1.13	0.69	-0.04
90	1.35	-0.10	-1.89	-0.71	-0.62	0.39	0.33	0.04	-2.14	0.47
91	0.82	-0.74	-0.38	-0.07	-0.60	0.67	-0.96	-0.33	-0.57	0.43
92	0.25	0.57	0.36	-0.38	-1.62	-1.60	2.79	1.06	-0.98	0.87
93	0.70	-0.37	0.81	-0.98	0.54	0.78	1.36	0.20	1.03	-2.13
94	0.04	-0.60	-0.14	0.68	-0.33	0.65	0.47	1.02	0.43	0.58
95	0.19	-1.10	-0.16	0.55	0.07	1.82	-1.35	-0.04	0.18	-1.52
96	0.40	-1.14	0.12	1.12	0.19	-0.30	-0.72	-0.72	0.44	1.23
97	-0.24	0.89	-0.45	-0.88	0.47	-0.73	0.14	-1.58	1.31	-1.14
98	1.39	1.65	-1.91	0.99	1.35	1.35	0.21	2.29	1.00	-1.12
99	1.05	-2.01	0.81	-1.18	-0.12	1.41	-0.35	-1.70	0.74	0.79
100	1.98	-0.53	1.06	-1.36	-0.20	-0.23	-0.75	-0.24	-0.74	-0.92

Table 4: Example of longtable spanning several pages

4.10 Sideways tables

Remember to insert `\usepackage{rotating}` in your LaTeX preamble. Sideways tables can't be forced in place with the 'H' specifier, but you can use the `\clearpage` command to get them fairly nearby. See Table 5.


```
> x <- x[1:30, ]  
> x.small <- xtable(x, label = "tabsmall", caption = "A sideways table")  
  
> print(x.small, floating.environment = "sidewaystable")
```

	1	2	3	4	5	6	7	8	9	10
1	0.17	0.60	-0.73	2.50	0.87	0.31	0.64	-1.02	-0.94	0.13
2	-0.32	-0.13	-0.13	0.46	-0.13	0.50	-1.03	1.28	0.90	0.18
3	0.50	-0.51	2.27	2.12	1.17	-0.11	-1.11	-0.10	-1.30	1.51
4	1.04	1.08	-0.44	-0.30	0.47	-0.03	1.28	-0.59	-0.11	-0.92
5	-0.77	-1.16	-0.22	0.32	0.92	0.51	1.68	-1.41	0.12	0.92
6	1.21	-0.11	-1.32	0.74	0.85	-0.23	0.12	-0.67	-0.87	-0.20
7	-1.02	-0.42	-1.39	1.12	1.35	0.13	0.90	-0.54	-0.72	-0.85
8	-0.23	-1.74	1.81	0.21	2.88	0.13	-0.25	0.57	-1.24	0.01
9	0.75	-1.94	0.05	-1.18	-0.53	-0.30	0.27	2.20	-0.68	-0.11
10	1.04	-0.85	-0.15	0.12	0.11	-1.18	-0.83	1.02	0.58	-0.24
11	0.57	-0.82	0.44	0.85	0.99	-1.13	1.42	0.14	0.62	0.72
12	0.63	-0.60	0.62	1.07	0.74	-0.41	-0.25	0.14	1.10	-0.27
13	0.08	0.06	0.63	-1.77	-0.38	0.23	-0.22	-0.94	-0.92	-0.41
14	0.37	1.23	-0.16	2.59	0.96	0.39	0.37	1.44	-0.69	-1.55
15	-0.22	0.41	1.10	-1.03	0.82	1.69	-1.80	1.09	-0.60	-0.21
16	0.40	-0.40	-0.23	0.66	-1.25	0.29	-1.42	-0.04	0.26	0.57
17	1.03	-0.25	0.68	-0.64	-1.44	1.72	0.38	1.94	-0.49	-0.14
18	-0.30	-0.04	-0.87	1.26	1.06	-0.57	0.51	0.80	0.56	-0.27
19	-1.11	-0.91	1.62	-1.96	-1.26	-0.29	0.63	0.69	0.37	-0.45
20	-1.49	-1.69	-0.39	-0.81	0.44	0.50	0.32	1.07	-0.22	0.75
21	-1.11	-1.25	1.20	0.53	-0.43	-0.64	-2.64	-0.06	0.73	-0.07
22	0.70	-1.28	1.46	-1.52	1.37	0.58	-1.25	0.30	1.49	0.40
23	-1.86	0.40	1.55	-2.04	-0.27	0.95	-1.29	-0.27	-1.59	-0.74
24	-1.06	0.91	-0.77	-2.86	-0.70	-0.26	-0.82	0.67	0.70	-0.95
25	0.30	-0.27	1.10	-0.35	0.31	0.49	-0.78	0.01	1.80	-2.56
26	-1.79	0.38	-0.98	-0.33	-0.89	0.09	0.82	1.02	0.82	0.57
27	-1.39	0.17	-0.96	-1.08	0.76	0.25	0.89	-3.11	-0.68	1.02
28	0.26	-0.40	1.13	0.17	0.53	0.38	0.81	0.83	-1.04	-0.23
29	-0.07	0.52	0.73	0.60	0.21	-0.69	-0.31	0.86	0.55	-0.60
30	-1.04	0.70	-0.65	0.92	0.16	-0.48	1.30	0.30	0.49	-0.12

Table 5: A sideways table

5 Acknowledgements

Most of the examples in this gallery are taken from the `xtable` documentation.

6 R Session information

```
> toLatex(sessionInfo())
```

- R version 2.9.1 (2009-06-26), x86_64-unknown-linux-gnu
- Locale: LC_CTYPE=en_US.UTF-8;LC_NUMERIC=C;LC_TIME=en_US.UTF-8;LC_COLLATE=en_US.UTF-8;LC_MONETARY=C;LC_MESSAGES=en_US.UTF-8;LC_PAPER=en_US.UTF-8;LC_NAME=C;LC_ADDRESS=C;LC_IDENTIFICATION=C
- Base packages: base, datasets, graphics, grDevices, methods, stats, tools, utils
- Other packages: xtable 1.5-6